

Rank® HTC3

Product description

Rank® HTC3 machine is specially designed for cogeneration applications with high-temperature thermal needs, and they can produce useful heat as hot water at 80°C.

In addition, by using heat at temperatures between 180 °C and 210 °C, this high efficiency machine is able to produce 145 kW_e.



A Rank® machine for every need

Whatever your need is, we have a Rank® machine that can be adapted to it, through a variety of products that cover a wide range of thermal and power applications.

LT1	MT1	HT1	HTC1
LT2	MT2	HT2	HTC2
LT3	MT3	HT3	HTC3
90°C	120°C	150°C	180°C 210°C

What is Rank®?

The Rank® equipment allows the production of electrical energy and useful heat using a low-temperature heat source, with the associated economic and environmental benefits.



Rank® HTC3


Applications

Among the main applications of the Rank® ORC machines, we highlight the waste heat recovery and the utilisation of renewable heat sources, with a special interest in cogeneration and trigeneration systems.

Heat sources



Industrial Waste Heat



Engines



Biomass



Solar CHP



Waste



Geothermal

Heat sinks



Cold Production



Heating




Industrial Processes



Drying

How it works?



- ① Evaporator** A heat exchanger that provides heat to the high-pressure working fluid and passes from subcooled liquid to superheated vapor (in the form of water or thermal oil).
- ② Turbine** The expansion of the superheated vapor is used to generate clean electricity.
- ③ Regenerator** To increase the efficiency of the system, the expanded working fluid is used to preheat the high-pressure liquid at the inlet of the evaporator.
- ④ Condenser** It produces useful heat (in the form of water) from the condensation of the working fluid at low pressure.
- ⑤ Pump** The pressure of the working fluid is increased, and the ORC cycle is completed.

Rank® HTC3


Rank® Technology

The Rank® equipment is composed of high quality, robust and efficient components, which offer the following advantages and benefits to our customers.



Rank® low rpm turbine

Operation at low revolutions reduces the noise level, lengthens the service life and improves the reliability.




Rank® direct drive

Direct drive avoids the use of gears or pulleys, minimising the maintenance and increasing electrical efficiency.



Zero leaks

Our hermetic components eliminate the leakage of the working fluid, reducing maintenance costs and downtime and being more environmentally friendly.



Magnetic transmission

Magnetic transmission to ensure the tightness and to reduce the possibility of leakage.



Rank® easy-connect

Electronics-free connection to the electricity grid at the required electrical quality conditions.



Flexible operation

Modular machines that can operate under a wide range of temperature and flow inlet and outlet conditions.



Digitalisation through the Rank® control system

Our machines operate without the need for the human interface through an automatic, efficient managing system.





Security

It complies with all safety regulations and minimises the risk of accidents.



Rank® service

Real-time remote monitoring and predictive control of the machines, and automatically generated reports.






Safety Regulations and Standards



- Low voltage Directive
- Machinery Directive
- Electromagnetic Compatibility Directive
- Pressurized Equipment Directive
- ENA ER G59/3
- ASME B31.1 – Power Piping Code, Mechanical
- ASME B31.3 – Process Piping Code
- ASME Boiler and Pressure Vessel Code Section VIII
- UL 508A- Control Panel Wiring
- EN/ISO 3744:2010

Rank® HTC3

Technical Data

	Heat source	Heat transfer fluid	Thermal Oil	-		
		Inlet temperature	180-210	°C		
		Outlet temperature	120-150	°C		
		Volumetric flow rate	44			
		Thermal power	1.200-1.600	kWt		
		Connections diameter	DN100 PN16	-		
		Pressure drop	50	kPa		
		Heat transfer fluid inner volume	125	L		
		Heat transfer fluid	Water	-		
		Inlet temperature	45-65	°C		
	Useful heat	Outlet temperature	60-80	°C		
		Volumetric flow rate	66			
		Thermal power	800-1.200	kWt		
		Connections diameter	DN150 PN16	-		
		Pressure drop	100	kPa		
		Heat transfer fluid inner volume	275	L		
			Electricity	Gross power	100-145	kWe
				Net power	80-115	kWe
				Voltage	3 x 400	V
				Frequency	50	Hz
Intensity	265			A		
Data Connection	RJ45			-		

Dimensions



A = 5.800 mm
 B = 2.250 mm
 C = 2.500 mm
 Weight 8.500 Kg

Rank® Pol. Ind. La Mezquita,
 Parcela 412 - nave B, 12600 La Vall d'Uixó,
 (Castelló) Spain
 Apartado de Correos 115,
 t. +34 964 696 859
 info@rankweb.es
 www.rankweb.es

Although our staff has made every effort possible to ensure the most accurate data and close to the final solution, these should be considered as indicative and not binding.